


### 配光曲線図


— A-A  
 — B-B  
 — C-C

光度 cd/1000lm



光度(cd/1000lm)			
	A-A	B-B	C-C
-180°	0	0	0
-170°	0	0	0
-160°	0	0	0
-150°	0	0	0
-140°	0	0	0
-130°	14	0	0
-120°	19	0	14
-110°	24	12	18
-100°	36	13	25
-90°	54	14	40
-80°	80	40	66
-70°	110	85	102
-60°	151	130	140
-50°	186	172	179
-40°	219	209	214
-30°	246	240	243
-20°	266	264	264
-10°	278	280	278
0°	283	283	283

光度(cd/1000lm)			
	A-A	B-B	C-C
0°	283	283	283
10°	278	280	278
20°	266	264	264
30°	246	240	243
40°	219	209	214
50°	186	172	179
60°	151	130	140
70°	110	85	102
80°	80	40	66
90°	54	14	40
100°	36	13	25
110°	24	12	18
120°	19	0	14
130°	14	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0



器具効率	最大取付間隔	保守率		
UP 7.7 %	A-A 1.28 H	良	中	否
DN 92.3 %	B-B 1.26 H	83	81	77

反射率 (%)	天井	80						70						50						30				0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	30	10	30	10	0
	床	30		10		30		10		30		10		30		10		30		10		0		
室指数	照明率 U ( × 0.01 )																							
0.6	44	35	29	42	34	28	43	34	28	41	33	28	41	33	28	39	32	27	32	27	32	27	24	
0.8	55	45	39	52	44	38	54	45	38	51	43	37	51	43	37	48	42	36	41	36	42	36	33	
1.0	64	54	47	59	51	45	62	53	46	58	50	45	59	51	45	55	49	44	49	43	49	44	40	
1.25	72	63	55	66	59	53	70	61	54	65	58	52	66	58	52	62	56	51	56	51	56	51	46	
1.5	79	69	62	72	64	58	76	68	61	70	63	58	71	64	58	67	61	56	61	56	61	56	51	
2.0	89	80	73	79	73	67	85	77	71	77	71	66	80	73	68	74	69	65	69	65	69	65	59	
2.5	95	87	80	84	78	73	92	84	78	82	77	72	85	79	74	79	74	70	75	71	74	70	64	
3.0	100	93	87	88	83	79	97	90	85	86	81	77	90	84	80	82	79	75	79	76	79	75	69	
4.0	107	101	96	93	89	85	103	98	93	91	87	84	95	91	87	87	84	81	85	82	84	81	75	
5.0	111	106	101	95	92	89	107	102	98	94	91	88	99	95	92	90	87	85	89	86	87	85	78	