



非常灯

名 称	非常用白熱灯専用形 (電池内蔵)
形 名	IEJ1302E3

保 守 率	0.79
光 束 換 算 係 数	1.00



光源	平常時	×
	非常時	JB3. 6V13W- Y46 × 1
光束	定 格	250 lm
	非常時	190 lm

前 面
下面開放
反射面
アルミ蒸着処理

備 考	
-----	--

光度 (cd/1000lm)						
θ \ φ	0° (A)	45° (C)	90° (B)	135° (C')	180° (A')	
0°	169					
10°	88					
20°	118					
30°	123					
40°	144					
50°	251					
60°	375					
70°	15					
80°	0					
90°	0					
100°	0					
110°	0					
120°	0					
130°	0					
140°	0					
150°	0					
160°	0					
170°	0					
180°	0					

器具直下からの各方向への指定照度が得られる距離 (m) (保守率、光束換算係数を含む)																
取付け高さ (m)		2.1	2.4	2.6	3.0	3.5	4.0	4.5	5.0	6.0	7.0	8.0	10.0	12.0	14.0	16.0
1	0°	4.0	4.3	4.6	4.2	2.0	0.5	0.3	-	-	-	-	-	-	-	-
	45°															
	90°															
	135°															
	180°															
0.5	0°	4.5	4.9	5.2	5.7	6.3	6.3	3.6	2.7	0.6	0.1	-	-	-	-	-
	45°															
	90°															
	135°															
	180°															
0.25	0°	4.9	5.5	5.8	6.4	7.1	7.8	8.4	8.9	8.4	3.9	1.0	0.1	-	-	-
	45°															
	90°															
	135°															
	180°															