



型番: MGLD3H291(TB)G/N-N8

配光曲線図

— A-A  
— B-B  
— C-C

光度(cd/1000m)			
	A-A	B-B	C-C
-90°	0	1	0
-80°	4	24	5
-70°	10	92	65
-60°	145	170	167
-50°	231	234	234
-40°	285	286	289
-30°	327	325	327
-20°	353	352	354
-10°	369	369	369
0°	374	374	374
10°	369	369	369
20°	353	352	354
30°	327	325	327
40°	285	286	289
50°	231	234	234
60°	145	170	167
70°	10	92	65
80°	4	24	5
90°	0	1	0



器具効率	最大取付間隔	保守率		
UP 0.0 %	A-A 1.25 H	良	中	否
99.9 %	B-B 1.25 H	95	92	87
DN 99.9 %				

反射率 (%)	天井		80						70						50						30						0
	壁		50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	30	10	30	10	0		
	床		30		10		30		10		30		10		30		10		30		10		0				
室指数		照度率 U ( × 0.01 )																									
0.6		50	41	35	47	40	35	49	41	35	47	40	34	48	40	35	46	39	34	39	34	39	34	32			
0.8		62	53	47	58	51	45	61	53	46	58	51	45	59	51	46	56	50	45	50	45	50	45	43			
1.0		71	62	56	66	59	54	70	61	55	65	58	54	67	60	54	64	58	53	58	54	58	53	51			
1.25		79	70	64	73	66	61	78	69	63	72	65	60	74	67	62	70	64	60	65	61	64	60	57			
1.5		85	76	70	77	71	66	83	75	69	76	70	65	79	73	67	74	69	65	70	66	69	65	62			
2.0		93	85	78	83	77	73	91	83	77	82	77	72	86	80	75	80	75	71	77	73	75	71	68			
2.5		98	91	84	87	82	77	96	89	83	86	81	77	91	85	80	84	79	76	81	77	79	76	72			
3.0		102	95	89	89	84	80	99	93	87	88	84	80	93	88	84	86	82	79	84	80	82	79	75			
4.0		105	100	95	92	88	84	102	96	92	91	87	84	97	92	88	89	85	82	88	84	85	82	78			
5.0		110	104	99	94	90	87	106	101	96	93	89	86	99	95	91	91	87	85	90	87	87	85	80			

株式会社ホタルクス