



型番: MPLD3H291(TB)G/N-N8

配光曲線図

— A-A  
— B-B  
— C-C

光度(cd/1000m)			
	A-A	B-B	C-C
-90°	0	1	0
-80°	4	24	5
-70°	10	92	15
-60°	146	170	168
-50°	231	235	234
-40°	285	286	290
-30°	328	325	327
-20°	354	353	354
-10°	369	369	369
0°	375	375	375
10°	369	369	369
20°	354	353	354
30°	328	325	327
40°	285	286	290
50°	231	235	234
60°	146	170	168
70°	10	92	15
80°	4	24	5
90°	0	1	0



器具効率	最大取付間隔	保守率		
UP 0.0 %	A-A 1.25 H	良	中	否
100.1 %	B-B 1.25 H	95	92	87
DN 100.0 %				

反射率 (%)	天井	80						70						50						30						0
		50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	30	10	30	10	0		
	座	30		10		30		10		30		10		30		10		30		10		30		10		0
室指数		照度率 U ( × 0.01 )																								
0.6		50	41	35	47	40	35	49	41	35	47	40	34	48	40	35	46	39	34	39	34	39	34	39	34	32
0.8		62	53	47	58	51	46	61	53	46	58	51	45	59	52	46	56	50	45	51	45	50	45	43		
1.0		72	62	56	66	59	54	70	62	55	66	59	54	68	60	54	64	58	53	59	54	58	53	51		
1.25		79	70	64	73	66	61	78	69	63	72	66	60	75	67	62	70	65	60	66	61	65	60	57		
1.5		85	76	70	77	71	66	83	75	69	76	70	65	80	73	67	75	69	65	70	66	69	65	62		
2.0		93	85	78	83	76	73	91	83	77	82	77	72	86	80	75	80	76	71	77	73	76	71	68		
2.5		99	91	84	87	82	77	96	89	83	86	81	77	91	85	80	84	79	76	81	77	79	76	72		
3.0		100	95	89	90	85	80	99	93	87	88	84	80	94	88	84	86	82	79	84	81	82	79	75		
4.0		100	100	95	93	88	84	104	98	93	91	87	84	97	93	88	89	86	82	88	85	86	82	78		
5.0		110	104	99	94	90	87	106	101	96	93	89	86	100	95	91	91	88	85	90	87	88	85	80		

株式会社ホテルクス